



LM-802FMGP-IL2

Industrial Managed Switch 8 * 10/100/1000 Base-T

The **LM-802FMGP-IL2** is a full Gigabit L2 managed industrial PoE Ethernet switch featuring 8 * 10/100/1000 Base-T PoE ports with up to 30W per port (total 120W) and 2 uplink 100/1000 Base-X SFP fiber ports. It intelligently delivers power to devices such as wireless APs, IP cameras, VoIP devices, and sensors while supporting L2 network management, IPv4 static routing, ACL/QoS policies, rich VLAN functions, and multiple redundancy protocols including STP/RSTP/MSTP and ERPS (<20ms convergence).



PRODUCT INTRODUCTION

Product Overview

The **LM-802FMGP-IL2 / LMI-HY2008GVP-SFP** is a full Gigabit L2 managed industrial PoE Ethernet switch independently developed by Lanmus. It has 8 × 10/100/1000 Base-T PoE ports. Ports 1-8 can support IEEE802.3af/at, with a maximum power of 30W per port and a total power of 120W. It also has 2 uplink 100/1000 Base-X SFP fiber ports.

It can automatically detect and recognize power-compliant devices that meet the standard and supply power through the network cable. It can supply power to PoE terminal equipment such as wireless APs, webcams, VoIP devices, and sensors through the network cable.

The **LM-802FMGP-IL2 / LMI-HY2008GVP-SFP** has L2 network management functions, supports IPv4 static route forwarding, and features a complete security protection mechanism, ACL/QoS policies, and rich VLAN functions, making it easy to manage and maintain.

It supports multiple network redundancy protocols including STP/RSTP/MSTP (<50ms), and the ERPS ring network function (convergence time <20ms) to improve link backup and network reliability, ensuring uninterrupted communication for critical applications.

According to actual application needs, routing address management, port management, port flow control, VLAN division, IGMP, security policy, and other application service configurations are performed through Web, CLI, SNMP, Telnet, and other network management methods.

The shell is made of aluminum alloy, providing excellent industrial field environmental adaptability, including mechanical stability, climate environment adaptability, and electromagnetic environment adaptability. The protection level is IP40, supporting dual redundant power supplies, low power consumption, and fanless operation. It comes with a 3-year warranty.

Gigabit Access & Integrated Bypass Function

- Support non-blocking wire-speed forwarding.
- Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.
- Support Gigabit Ethernet port and Gigabit SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- Support physical single-mode single fiber optical path (Bypass) function, pure hardware switching, short switching time, does not affect the data transmission rate and improves the stability of the network system.

Network Management & Fast Ring Function

- STP/RSTP/MSTP/ERPS.
- Static and dynamic aggregation.
- IEEE802.1Q VLAN, flexible VLAN division, Access, Trunk and Hybrid
- QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including EQU, SP, WRR & SP+WRR.
- IGMP Snooping V1/V2/V3 meets multi-terminal high-definition video surveillance and video conference access requirements.
- ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.

Security

- 802.1X authentication.
- Port isolation, storm control.
- IP-MAC-VLAN-Port binding.

LM-802FMGP-IL2 / LMI-HY2008GVP-SFP

Stable & Reliable

- CE, RoHS.
- Low power consumption, No fan, aluminum shell.
- The user-friendly panel can show the device status through the LED indicator of PWR, SYS, Link, L/A.

Easy Operation & Maintenance Management

- HTTPS, SSLV3, and SSHV1/V2.
- RMON, system log, LLDP, and port traffic statistics.
- CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).

SPECIFICATION

MODEL	LM-802FMGP-IL2 / LMI-HY2008GVP-SFP
INTERFACE CHARACTERISTICS	
Fixed Port	8 * 10/100/1000 Base-T PoE ports 2 * 100/1000 Base-X uplink SFP slot ports 1 * RS232 console port
Ethernet Port	Port 1-8 support 10/100/1000 Base-T auto-sensing, full/half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10 BASE-T: Cat3,4,5 UTP(≤100 meters) 100 BASE-TX: Cat5 or later UTP(≤100 meters) 1000 BASE-T: Cat5e or later UTP(≤100 meters)
SFP Slot Port	Gigabit SFP optical fiber interface, default no include optical modules.
Wavelength/Distance	multimode: 850nm 0~550M,1310nm 0~2KM single mode: 1310nm 0~40KM, 1550nm 0~120KM

SPECIFICATION

MODEL	LM-802FMGP-IL2 / LMI-HY2008GVP-SFP
CHIP PARAMETER	
Network Management Type	L2
Ring Network	Supports ERPS ring network function, with a maximum number of rings of 11 and a convergence time of <20ms
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100BaseTX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3ae 10GBase-LR/ SR, IEEE802.3x
Switching Capacity	20Gbps
Forwarding Mode	Store and Forward(Full Wire Speed)
Buffer Memory	14.88Mpps
MAC	8K
LED Indicator	• Power Indicator Light, P1 : 1 Green • Fiber Indicator Light, F : 1 Green • On the seat • Yellow: Indicate PoE • Green: Indicates network working status
Reset	Yes, Press and hold the reset switch for 5s and release it to restore the factory settings
POWER	
Power Supply	DC : 52V/2.3A 120W
PoE output power	IEEE802.3af/at, with a maximum power of 30W per port and a total power of 120W
PoE Power Supply Method	Supports 1,2+, 3,6-power supply

SPECIFICATION

MODEL	LM-802FMGP-IL2 / LMI-HY2008GVP-SFP
CERTIFICATION & WARRANTY	
Lightning Protection	Lightning protection: 6KV 8/20us, Protection level: IP40 IEC61000-4-2(ESD):±8kV contact discharge, ±15kV air discharge IEC61000-4-3(RS):10V/m(80~ 1000MHz) IEC61000-4-4(EFT): power cable:±4kV; data cable:±2kV IEC61000-4-5(Surge):power cable:CM±4kV/DM±2kV; data cable: ±4kV IEC61000-4-6(radio frequency transmission): 10V(150kHz~80MHz) IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m , 1s to 3s IEC61000-4-9(pulsed magnet field):1000A/m IEC61000-4- 10(damped oscillation):30A/m 1MHz IEC61000-4- 12/ 18(shockwave):CM 2.5kV,DM 1kV IEC61000-4- 16(common-mode transmission): 30V; 300V, 1s IEC61000-6-2(Common Industrial Standard)
Mechanical Properties	IEC60068-2-6 (anti vibration), IEC60068-2-27 (anti shock) IEC60068-2-32 (free fall)
Certification	CE mark, commercial, CE/LVD EN62368- 1, ROHS
PHYSICAL PARAMETER	
Operation TEMP/ Humidity	-40~+75°C;5%~90% RH Non condensing
Storage TEMP/ Humidity	-40~+85°C;5%~95% RH Non condensing
Dimension (L*W*H)	172mm* 145mm*55mm
Installation	Desktop, DIN rail

SPECIFICATION

MODEL	LM-802FMGP-IL2 / LMI-HY2008GVP-SFP
L2 FUNCTIONS	
Port configuration	Auto-negotiation Flow Control Port Mirror: TX/RX/BOTH; Many-to-1 monitor Traffic statistics
Link Aggregation	Static link aggregation LACP Algorithm based on Source/Destination MAC Algorithm based on Source/Destination IP
MAC Table	Aging Time Static MAC address Dynamic MAC address management
QoS	port-based CoS 802.1p-based CoS DSCP-based Scheduling algorithms SP, WRR, SP+WRR Storm Control (Broadcast, Multicast, Unknown Unicast) Bandwidth control per port
NETWORK MANAGEMENT FEATURES	
VLAN	4094 Active VLANs 4094 VID 802.1Q Tag VLAN Port VLAN Protocol VLAN MAC VLAN Voice VLAN 802.1ad Q-in-Q tunneling Private VLAN (Protected port) GARP/GVRP
ACL	256ACLs L2, L3 e L4 Time-based ACL

SPECIFICATION

MODEL	LM-802FMGP-IL2 / LMI-HY2008GVP-SFP
NETWORK MANAGEMENT FEATURES	
Spanning tree	802.1D Spanning Tree Protocol (STP) 802.1w Rapid Spanning Tree Protocol (RSTP) 802.1s Multiple Spanning Tree Protocol (MSTP) Loop Guard Root Guard TC-BPDU Guard BPDU Guard BPDU Filter
Multicast	256 groups IGMP v1/v2/v3 Snooping, Fast Leave MLD Snooping Multicast VLAN
Other Features	DNS Client DHCP Relay DHCP Client DHCP Snooping DHCP Option 82 SNTP Client UDLD
PoE management	Soft-Reboot PoE Non-stop Total PoE Per port PoE function enable/disable PoE classification detection PD alive check PoE schedule
Maintenance	Cable Diagnostics Ping SFP DDM(Digital Diagnostics Monitoring) Thermal protection System log (Local and Remote) Memory and CPU Monitoring

SPECIFICATION

MODEL	LM-802FMGP-IL2 / LMI-HY2008GVP-SFP
NETWORK MANAGEMENT FEATURES	
L2 functions	IPV4 Equal Cost Routing NG protocol, maximum 1000 entries ARP protocol, maximum 1000 entries Pingv6, Telnetv6, TFTPv6, DNSv6, ICMPv6 IPV4/IPV6 VRRP, the maximum group is 255 IPV4/IPV6 VLANIF interface supports up to 128 IPV4/IPV6 static route/default route supports up to 128 entries L2 network management function, IPV4/IPV6 dual-stack management.



Industrial Managed Switch

DATA SHEET
LM-802FMGP-IL2



LANMUS.COM